



## PROFILI APERTI A "C"



Dimensioni B H C mm.	Spessore mm.						
	1,5	2	2,5	3	3,5	4	5
	Peso Kg/m						
30 10 10	1,11	1,39	1,39				
40 10 10	0,99	1,24	1,24				
40 15 15		1,46	1,46				
40 15 15	1,58	2,02	2,02	2,78			
50 15 15	1,46	1,87	1,87				
50 20 20	1,58	2,02	2,02	2,78			
50 15 15	1,70	2,18	2,18	3,02			
60 15 15		2,02	2,02	2,78			
60 20 20		2,49	2,49	3,49			
80 20 20		2,81	2,81	3,96			
100 25 25		3,59	3,59	5,14	5,85	6,52	
120 30 30		4,38	4,38	6,32	7,22	8,09	9,69

Disponibili anche zincati

## OMEGA SIMMETRICI



Dimensioni B x A x C	Spessore mm.					
	1,5	2	2,5	3	3,5	4
	Peso Kg/m					
30 50 10	1,93	2,54	3,14			
30 50 12	2,00	2,62	2,94			
40 60 15		3,17	3,92	4,66		
40 80 20		3,80	4,71	5,60		
50 100 20		4,74	5,88	7,01		
60 120 25			6,86	8,20		
80 150 50				10,50		

Disponibili anche zincati